



FEATURE LIST

- 2.4GHZ, high quality color CMOS sensor for crisp, clear images
- Weatherproof with sturdy Alloyed Shell for Outdoor use
- Built-in Infra-Red (26x LED): Color during day, Nightvision (B&W) at night
- Built-in microphone for audio monitoring
- Long operation range: up to 100 m line of sight or 30 m through obstructions (walls/ceilings)

The camera specification	Imaging sensor: 1/4" CMOS
	CMOS total pixels: Pal 628 x 582; NTSC 510 x 492
	Horizontal resolution: 380TV lines
	View angle: 62
	Minimum illumination: 0 Lux / F1.5
	Gain control: automatic
	Frequency: ISM 2,400MHz ~ 2,483MHz 4CH
	Transmission power: FM
	Modulation mode: 10mW
	Bandwidth: 18MHz
	Bandwidth: 18M
	Operating temperature: -10C ~ +50C / 14F ~ 122F
	Storage temperature: -40C ~ -85C / -40F ~ +185F
	Unobstructed effective range: 100 m
	Channel frequency: CH1=2414; CH2=2432; CH3=2450; CH4=2468 (MHz)
	Dimension(WxLxH): 65x70x136 mm
Weight: 350 g	



FEATURE LIST

- 2.4GHZ, High quality Color CMOS sensor for crisp, clear images
- Built-in microphone for audio monitoring
- have 6 led light for night vision function
- Long operation range: up to 100 m clear line of sight or 30 m through walls/ceilings
- Metal crust housing with adjustable focus lens
- Easy to install: wall/ceiling mountable

The camera specification	Imaging sensor: 1/4" CMOS
	CMOS total pixels: Pal 628 x 582; NTSC 510 x 492
	Horizontal resolution: 380TV lines
	View angle: 62
	Minimum illumination: 0 Lux / F1.5
	Gain control: automatic
	Frequency: ISM 2,400MHz ~ 2,483MHz 4CH
	Transmission power: FM
	Modulation mode: 10mW
	Bandwidth: 18MHz
	Bandwidth: 18M
	Operating temperature: -10C ~ +50C / 14F ~ 122F
	Storage temperature: -40C ~ -85C / -40F ~ +185F
	Unobstructed effective range: 100 m
	Channel frequency: CH1=2414; CH2=2432; CH3=2450; CH4=2468 (MHz)
Dimension(WxLxH): 65x70x136 mm	
Weight: 140 g	



FEATURE LIST

- Dual Output Mode: USB for PC and AV for TV/Monitor
- Built-in microphone for audio monitoring
- 4-channel operation allows multiple (1-4) camera systems (optional)
- Long operation range: up to 100 m clear line of sight or 30 m through walls/ceilings
- Compact, Lightweight and Super Mini size
- Supports Windows 98/2000/XP MSN Messenger
- High speed MPEG 4 compression ,support real time image output.

Receiver Specification	Frequency: ISM 2,400 - 2,483MHz
	Antenna: Omni-directional antenna
	Channel: 1-4 (Flip-type switch)
	Intermediate Frequency: 480MHz
	Frequency Stabilization: +/- 100KHz
	Demodulation Mode: FM
	Receiving Sensitivity: \leq -85dBm
	Video Output: 1Vp-p@75 ohm, S/N>38dB
	Audio Output: 1Vp-p@600 ohm
	Power: DC 5V
	Operating Temperature: -10oC ~ +40oC
	Operating Humidity: 85%RH
	Dimension(WxLxH): 80x68x16 mm
Weight: 200 g	